

Transporter

Engineered for rugged performance, it delivers reliable loading of bulk materials in even the most demanding environments.



Features & Benefits

- Heavy Duty Mild Steel Construction
- Fast acting air controls
- Designed in Accordance with and Certified as an ASME Pressure Vessel
- High Level Probe
- 60° Cone Angle
- Tangential Jets to Promote Material Flow & Aeration
- Delivered Fully Assembled and Factory-Tested

Specifications

- Controls: 24 VDC / 120 VAC
- Compressed Air: Clean & Dry at 100 PSIG

DIMENSIONS		
CAPACITY	OVERALL HEIGHT A	OUTER DIAMETER
5 FT ³	5'-4 3/4"	24"
10 FT ³	6'-3"	30"
20 FT ³	7'-3"	42"
30 FT ³	8'-4"	42"
40 FT ³	8'-9 3/8"	48"
50 FT ³	9'-1 3/8"	54"
60 FT ³	9'-7 3/8"	60"
70 FT ³	10'-1 3/8"	60"
80 FT ³	10'-3 1/2"	66"
90 FT ³	10'-8 1/2"	66"
100 FT ³	10'-10 5/8"	72"
110 FT ³	11'-2 5/8"	72"
120 FT ³	11'-6 5/8"	72"
130 FT ³	11'-11 5/8"	72"
140 FT ³	12'-3 5/8"	72"
150 FT ³	12'-7 5/8"	72"

Options

- Stainless Steel Construction for corrosive or sanitary environments
- Hazardous Location Components for compliance in classified areas
- High Temperature Design for heat-sensitive applications
- Abrasion Resistant Linings
- Custom Heights, Inlets, Outlets to suit facility layout